


## 技术规格 Technical specifications

1. 材质 Material: DTT-P4

2.. 尺寸和磁芯参数 Size and Core parameters

	尺寸 Size(mm)		
	A	50.0+1.2/-0.7	
	B	14.6±0.4	
	C	9.0±0.3	
	磁芯参数 Core parameters		
有效磁路长度 Effective Length Le			
有效截面积 Effective Cross Area Ae			
有效体积 Effective Volume Ve			
参考重量 Approx. Weight Wt		32g/pcs.	

3. 电气特性 Electrical characteristics

项目 Item	规格 Spec	测试条件 Testing Condition	测试仪器 Testing Instrument
$\mu i$	2400±25%	1kHz 0.25V 25℃	Agilent4284A
Pcv	≤500kW/m <sup>3</sup>	100kHz 200mT 100℃	BsT- LMG610

注：以上数据依据相同材料的磁环测试

The above data are based on the magnetic ring test data of the same batch of materials

4. 允许最大缺陷（外观）Maximum chip off:

		接合面 Joint face	其他表面 Other surface
破损 broken	1 处破损的面积 1 The damaged area	≤1mm <sup>2</sup>	≤2mm <sup>2</sup>
	2 处以上破损面积的合计 More than two cut area combined	≤2mm <sup>2</sup>	≤4mm <sup>2</sup>
	破损深度 Damage depth	≤0.5mm	≤1mm
裂纹 cracks	深度 depth	≤0.3mm	≤0.5mm
	长度 length	≤延长线长度的 1/4 Extension of line length 1/4	≤延长线长度的 1/3 Extension of line length 1/3
其他 other	无有害毛刺，气孔等 No harmful burr, porosity, etc		

Item:	P/N:	SPEC./N
FERRITE CORE	P4I50/15/9	P4 10501-22211.1